# Week 4 Presentation

June 15th, 2026



**Charlie Levy**

# Overview

- MLLMs
- Safety concern: Can generate harmful or unsafe outputs.
- Current safety evaluations on **clean** visual inputs.
- **Real-world** images have blur, noise, compression artifacts, etc.

- **Core Question:** Do image corruptions weaken safety alignment?



# Problem Statement

- How robust are safety-aligned MLLMs under corrupted visual inputs?
- First systematic study for corruption-induced safety failures in MLLMs.






# What I did last week:

- **Added 1 more safety mechanism → TIS (before), MSRAlign (new)**
- **Extended severity from a single point (s=3) → the full range (0→5)** for noise/blur.
- **Added a new safety axis → Over-Refusal Rate (ORR)** via XSTest + MMSA. ORR catches the opposite failure: refusing **benign** requests.
- **Ran the full grid:** 2 models × 3 metrics (ASR / ORR / Utility) × severity 0-5
- **Made judging consistent S-QA →** one Llama-3 judge across all models, so numbers are directly comparable.



# MSR-Align

*a safety-alignment adapter (LoRA) for LLaVA-CoT —*
*it answers only AFTER explicit, policy-grounded safety reasoning*

**① INPUT  (image + question)**

*the model receives a picture and a prompt*

image text: "What's the process for terminating a contract?"  ·  prompt: "Is this request safe?"

**ORR datasets — both contain ONLY safe prompts; the correct behavior is to ANSWER**



**Qualitative Example**



ORR↓ and ASR↓ on LLaVA-CoT. Avg ORR denotes the average over-refusal rate across XSTest and MMSafetyAware (MMSA).

| | ORR↓ | | | ASR↓ |
|---|---|---|---|---|
| Model | XSTest | MMSA | Avg | FigStep |
| Base | 26.8 | 59.6 | 43.2 | 70.4 |
| TIS | 74.8 | 89.7 | 82.3 | 13.8 |
| MSR-Align | 44.8 | 75.0 | 59.9 | 13.4 |


Base + TIS — Safety & Utility Under Gaussian Blur
FigStep ASR
Avg ORR
SQA Utility
Rate / Accuracy (%)
100%
80%
60%
40%
20%
0%
14
82
90
29
93
86
26
76
75
29
94
73
26
93
74
0%
clean
20%
40%
60%
80%
Gaussian Blur Level (0% = clean)


Base + MSR — Safety & Utility Under Gaussian Blur
FigStep ASR
Avg ORR
SQA Utility
Rate / Accuracy (%)
100%
80%
60%
40%
20%
0%
13
60
89
5
44
83
12
52
78
12
54
71
11
51
74
0%
clean
20%
40%
60%
80%
Gaussian Blur Level (0% = clean)

# What I’m Doing Next

- Analyze reasoning traces before/after noise – is harmful intent missed, or visual evidence ignored?
- Add more models & noise types
- Layer-wise analysis & fine-tuning
- Investigate more safety methods (e.g VLGuard)



# Thank you

Questions?