Week 7 Presentation

July 6th, 2026



Charlie Levy

Overview

Core of my project: Testing whether everyday image corruptions break the safety of MLLMs.





SIUO ASR with 4 different VLMs



The two reasoning models have different parseable structures

- *LLaVA-CoT =*
  - *<SUMMARY>*
  - *<CAPTION>*
  - *<REASONING>*
  - *<CONCLUSION>*

- *R1-Onevision =*
  - *<think>...</think> + answer*



Reasoning increases ASR, but not much more than w/ clean



Set up safety fine-tuning w/ LLaMA-Factory

- Built a new training environment
- Fine-tuned LLaVA-CoT on the safety dataset Think-in-Safety (TIS)
- Trained clean and with image corruptions checkpoints
  - Copied the TIS dataset and blurred / added snow to the images randomly
  - 25% Clean, 25% Glass Blur, 25% Snow, 25% Zoom Blur



TWO TIS CHECKPOINTS TRAINED

Clean reproduces the reference almost exactly; corrupted differs only by a small, expected offset

Clean TIS checkpoint – matches my mentor's

- Same recipe, same size: 26.2M trained params, identical 825 steps
- Loss curve overlaps almost exactly – within 0.005 the whole way
- Final loss 1.5930 vs mentor's 1.5929 → basically identical
- Confirms my whole setup is correct



Ran the SIUO corruption test

- 2 corruptions × 2 models (my checkpoints) = 4 runs
- 167 answers each – all complete, none empty
- Saved locally, ready for scoring
- 4 / 4 runs finished
- 668 answers collected



Up next

- Score the new SIUO answers with the safety adapters
- Compare clean-trained vs corruption-trained models
- See if training on corruptions makes them safer
- Evaluate on lower severities for corruptions
- Analyze results and, if required, change training pipeline



Thank you

Questions?

